


Product Features

N Female to RG-316 cable using RG Type Flex 12 Coax, 0.098 inches long, and Operating to 0.4 GHz.



Electrical Specification: T_{Ambient} = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		6.0	
VSWR	DC to 0.4	1:			1.2	
	0.4 to 1.0				1.25	
	1.0 to 2.4				1.3	
	2.4 to 5.0				1.35	
Insertion Loss	DC to 0.4	dB/ft.			0.18	
	0.4 to 1.0				0.31	
	1.0 to 2.4				0.49	
	2.4 to 5.0				0.67	
Velocity Of Propagation		%		69.5		

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	SMA Male	
Connector 1 Coupling Nut	Gold Plated Brass	
Connector 1 Body	Gold Plated Brass	
Connector 1 Contact	Gold Plated Brass	
Connector 2	N Female	
Connector 2 Coupling Nut	None	
Connector 2 Body	Tin-Zinc-Copper-Alloy Plated Brass	
Connector 2 Contact	Gold Plated Beryllium Copper	
Coax Cable	RG Type Flex	
Cable Type	RG-316	
Cable Inner Conductor	7/.0067 SPCW	
Dielectric	PTFE	
Shield	1. SPC Braid	
Jacket	FEP	
Coax Diameter	0.098	
Minimum Bend Radius	0.5	
Length	12.0	

SMA Male to N Female cable using RG-316 RG Type Flex Coax, 12 inches long, and
Operating to 6 GHz.

Parameter	Description	Notes
Operating Temperature	-55.0 to 200.0 °C	
RoHS Compliance	Yes	

Product Notes